


SI...ET-2RS(d 15□80)



auswählen	Anfrage	Lager Nr.	Abmessungen (mm)															Tragfähigkeit (kN)		Gewicht kg
			d3	B	d _k	C ₁ max	d ₂	G 6H	h ₁	l ₃ s min	l ₄	l ₅	l ₇	W	d ₃	d ₄	rs min	a°	Kr	
SI15ET-2RS	15	12	22	10.5	40	M14	61	30	81	8	21	21	21	26	0.3	8	25	36	0.16	
SI17ET-2RS	17	14	25	11.5	46	M16	67	34	90	10	24	27	25	29	0.3	10	32	45	0.24	
SI20ET-2RS	20	16	29	13.5	53	M20×1.5	77	40	103.5	10	25.5	30	28	34	0.3	9	45	60	0.35	
SI25ET-2RS	25	20	35.5	18	64	M24×2	94	48	126	12	33	36	35	42	0.6	7	85	83	0.66	
SI30ET-2RS	30	22	40.7	20	73	M30×1.5	110	56	146.5	15	37.5	46	42	50	0.6	6	110	110	0.98	
SI35ET-2RS	35	25	47	22	82	M36x3	125	60	166	15	40	55	48	58	0.6	6	140	146	1.5	
SI40ET-2RS	40	28	53	24	92	M39x3	142	65	188	18	47	60	52	65	0.6	7	175	180	2.1	
SI45ET-2RS	45	32	60	28	102	M42x3	145	65	196	20	52	65	58	70	0.6	7	225	240	2.7	
SI50ET-2RS	50	35	66	31	112	M45x3	160	68	216	20	57	70	62	75	0.6	6	275	290	3.5	
SI60ET-2RS	60	44	80	39	135	M52x3	175	70	242.5	20	68.5	80	70	88	1	6	430	450	5.6	
SI70ET-2RS	70	49	92	43	160	M56x4	200	80	280	20	81	85	80	98	1	6	550	610	8.3	
SI80ET-2RS	80	55	105	48	180	M64x4	230	85	320	25	91	95	95	110	1	6	705	750	13	