


# SIJ...(d 5-22)



auswählen	Anfrage	Lager Nr.	Abmessungen (mm)														Tragfähigkeit (kN)			Gewicht kg
			d3	B	dk	C1 max	d2	G	h1	l3 s min	l4	l5	W	d3	d4	rs min	a°	Kr	Kor	
SIJ5	5	8	11.112	7	16	M5	27	12.5	35	4	10	9	12	0.3	7	2.3	5.9	0.016		
SIJ6	6	9	12.7	7	18	M6	30	13.5	39	5	11	10	13	0.3	11	3.2	6.5	0.02		
SIJ8	8	12	15.875	9	22	M8	36	16	47	5	14	12.5	16	0.3	14	5.3	8	0.037		
SIJ10	10	14	19.05	11	26	M10	43	19.5	56	6.5	17	15	19	0.3	12	7.3	10.5	0.061		
SIJ12	12	16	22.225	12	30	M12	50	24	65	6.5	19	17.5	22	0.3	13	8.5	13	0.089		
SIJ14	14	19	25.4	14	34	M14	57	27	74	8	22	20	25	0.3	14	12	17	0.135		
SIJ16	16	21	28.575	15	38	M16	64	33	83	8	22	22	27	0.3	15	16.5	21	0.171		
SIJ18	18	23	31.75	17	42	M18x1.5	71	36	92	10	27	25	31	0.6	14	20	25.5	0.246		
SIJ20	20	25	34.925	18	46	M20x1.5	77	40	100	10	30	27.5	34	0.6	14	23	30	0.314		
SIJ22	22	28	38.1	20	50	M22X1.5	84	43	109	12	32	30	37	0.6	15	27.5	35.5	0.41		