


SABP...S(d 5□30)



auswählen	Anfrage	Lager Nr.	Abmessungen (mm)											Tragfähigkeit		Gewicht (kg)
			d3	d ₃ 6g	B	C1	$\frac{l_1}{s}$ min	d ₁	d ₂	h	l ₂	d _k	R _{1s}	eine	Kr	
SABP5S	5	M5x0.8	8	6	20	7.7	16	33	41	11.11	0.3	13	3.25	5.7	0.013	
SABP6S	6	M6x1.0	9	6.75	22	8.96	18	36	45	12.7	0.3	13	4.3	7.2	0.02	
SABP8S	8	M8x1.25	12	9	25	10.4	22	42	53	15.875	0.3	14	7.2	11.6	0.03	
SABP10S	10	M10x1.5	14	10.5	29	12.9	26	48	61	19.05	0.3	13	10	14.5	0.055	
SABP12S	12	M12x1.75	16	12	33	15.4	30	54	69	22.225	0.3	13	13.4	17	0.085	
SABP12S/B2	12	M12x1.25	16	12	33	15.4	30	54	69	22.225	0.3	13	13.4	17	0.085	
SABP14S	14	M14x2.0	19	13.5	36	16.9	34	60	77	25.4	0.3	16	17	24	0.14	
SABP16S	16	M16x2.0	21	15	40	19.4	40	66	86	28.575	0.3	15	21.6	28.5	0.21	
SABP16S/B1	16	M16x1.5	21	15	40	19.4	40	66	86	28.575	0.3	15	21.6	28.5	0.21	
SABP18S	18	M18x1.5	23	16.5	44	21.9	44	72	94	31.75	0.3	15	26	42.5	0.28	
SABP20S	20	M20x1.5	25	18	47	24.4	50	78	103	34.925	0.3	14	31.5	52.5	0.38	
SABP22S	22	M22x1.5	28	20	51	25.8	54	84	111	38.1	0.3	15	38	57	0.48	
SABP25S	25	M24x2.0	31	22	57	29.6	60	94	124	42.86	3	15	47.5	68	0.64	
SABP28S	28	M27x2.0	35	24	62	32.3	66	103	136	47.63	0.3	15	58	75.5	0.96	
SABP30S	30	M30x2.0	37	25	66	34.8	70	110	145	50.8	0.3	17	64	88	1.1	