


SI...C(d 5□30)



auswählen	Anfrage	Lager Nr.	Abmessungen (mm)														Tragfähigkeit (kN)		Gewicht kg	
			d3	B	dk	C ₁ max	d ₂	G 6H	h ₁	l ₃ s min	l ₄	l ₅	l ₇	W	d ₃	d ₄	rs min	a°		Kr
SI5C	5	6	10	4.5	21	M5	30	11	40.5	5	11.5	10	10	13	0.3	13	3.6	8.1	0.021	
SI6C	6	6	10	4.5	21	M6	30	11	40.5	5	11.5	11	11	13	0.3	13	3.6	8.1	0.021	
SI8C	8	8	13	6.5	24	M8	36	15	48	5	13	13	13	16	0.3	15	5.8	12.9	0.039	
SI10C	10	9	16	7.5	29	M10	43	20	57.5	6.5	15	16	16	19	0.3	12	8.6	17.6	0.065	
SI12C	12	10	18	8.5	34	M12	50	23	67	7	18	18	19	22	0.3	10	11	24.5	0.096	
SI15C	15	12	22	10.5	40	M14	61	30	81	8	21	21	21	26	0.3	S	18	36	0.16	
SI17C	17	14	25	11.5	46	M16	67	34	90	10	24	27	25	29	0.3	10	22	45	0.24	
SI20C	20	16	29	13.5	53	M20x1.5	77	40	103.5	10	25.5	30	28	34	0.3	9	31	60	0.35	
SI25C	25	20	35.5	18	64	M24x2	94	48	126	12	33	36	35	42	0.6	7	51	83	0.66	
SI30C	30	22	40.7	20	73	M30x2	110	56	146.5	15	37.5	46	42	50	0.6	6	65	110	0.98	