


SIA...ES(d 25÷160)



auswählen Anfrage			Lager Nr.	Abmessungen (mm)														Tragfähigkeit (kN)		Screw	Gewicht kg
				d3	B	d _k	C ₁	d ₂	G 6H	h ₁	l ₃	l ₄	l ₇	d ₄	d ₆	b	r _s	a°	Kr		
SIA25ES	25	20	35.5	23	56	Ml 8x2	65	30	95	29	28	48	21	0.6	7	48	72	M8x20	0.62		
SIA30ES	30	22	40.7	28	64	M24x2	75	35	109	34	34	56	26	0.6	6	62	106	M8x25	0.88		
SIA35ES	35	25	47	30	78	M30x2	90	46	132	40	45	65	28	0.6	6	79	153	M10x30	1.52		
SIA40ES	40	28	53	35	94	M39x3	105	56	155	44	56.5	77	33	0.6	7	99	250	M12x35	2.43		
SIA50ES	50	35	66	40	116	M50x3	135	76	198	55	70	88	36	0.6	6	156	365	M12x35	4.75		
SIA60ES	60	44	80	50	130	M64x3	170	96	240	65	87	118	46	1	6	245	400	M16x45	8.55		
SIA70ES	70	49	92	55	154	M80x3	195	112	277	75	110	128	51	1	6	313	540	M16x50	12.24		
SIA80ES	80	55	105	60	176	M90x3	210	122	305	80	128	156	55	1	6	400	670	M20x55	18.35		
SIA90ES	90	60	115	65	210	M100x3	250	142	365	90	152	167	60	1	5	488	980	M20x60	31.56		
SIA100ES	100	70	130	70	230	M110x4	275	150	400	105	170	171	65	1	7	607	1120	M20x60	34		
SIA110ES	110	70	140	80	264	M120x4	300	160	442	115	180	187	75	1	6	654	1700	M24x75	44		
SIA120ES	120	85	160	90	340	M150x4	360	192	540	140	210	240	85	1	6	950	2900	M24x85	75		
SIA140ES	140	90	180	110	380	M160x4	420	210	620	185	230	244	105	1	7	1070	3350	M30X100	160		
SIA160ES	160	105	200	110	480	Ml 80x4	460	220	710	200	260	268	105	1	8	1360	4302	M30x100	185		